



Freestanding and flexible graphene paper as support for biocatalysts in enzymatic biofuel cells

Shen, Fei; Pankratov, Dmitrii; Zhang, Jingdong; Ulstrup, Jens; Chi, Qijin

Publication date:
2018

[Link back to DTU Orbit](#)

Citation (APA):

Shen, F., Pankratov, D., Zhang, J., Ulstrup, J., & Chi, Q. (2018). *Freestanding and flexible graphene paper as support for biocatalysts in enzymatic biofuel cells*. Abstract from 3rd Summer Meeting on Bio-Electrochemistry, Antwerpen, Belgium.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Freestanding and flexible graphene paper as support for biocatalysts in enzymatic biofuel cells

Fei Shen, Dmitry Pankratov, Jingdong Zhang, Jens Ulstrup and Qijin Chi

NanoChemistry Group, Department of Chemistry, Building 207, Technical University of Denmark, DK-2800 Kongens Lyngby, Denmark.

Biocatalysts for enzymatic biofuel cells (EBFCs) require more practicable and spendable electrode materials for accommodation of the enzymes than the traditional solid graphite or expensive noble metal electrodes. We report here the use of novel graphene paper (GP) as a freestanding and flexible cathode and anode electrode material for immobilization of enzymes in a glucose/O₂ EBFC. GP electrodes were prepared via controlled assembly of graphene oxide (GO) nanosheets into a freestanding structure, followed by the specific reduction of GO to reduced GO (rGO). Bilirubin oxidase (BOx) physically adsorbed on the GP electrode, can directly transfer electrons between BOx and the cathode, facilitating the dioxygen reduction reaction (ORR). Likewise, pyrroloquinoline quinone dependent glucose dehydrogenase (PQQ-GDH) was physically immobilized onto a GP anode. However, direct electron transfer between PQQ-GDH and the anode cannot occur because the active site of the enzyme is deeply buried in the protein structure. Meldola blue (MB) was therefore introduced as a mediator shuttling electrons between PQQ-GDH and the anode, and facilitating PQQ-GDH catalysed glucose oxidation. As a result, an EBFC with a robust open circuit voltage up to 0.625 V and max power density of 3.97 $\mu\text{W}/\text{cm}^2$ could be obtained. These values are competitive with established EBFCs. The new GP supported EBFC holds potential for operating under *in vivo* conditions, e.g. integrated in biological compartments, and with minimal risk of blood clotting and plaque formation, and driving a low-power device such as a pacemaker.